













What makes the 170-22 stand out

- One of the fastest blindstitch machines in the world, which is only surpassed in speed by a different model from us, for universal use in men's-, women's clothing and in the curtain industry .
- The wide range of accessories makes the machine an all-rounder in hem and facing processing. From the thinnest suit fabrics to the hemming of winter coats, this machine can be used!
- The use of the spring-loaded plunger and the possibility of changing to a different plunger shape also enables the processing of thick cross seams and materials that are sensitive to marking.
- Equipped with new drive from Dürkopp Adler. The DAC Classic control box and the DA432 drive are used together with the OP-1000 control panel. This package ensures more user-friendly operation.
- Large arm clearance of 220mm x 110mm.

Options available on request:

Technische Daten / Technical data		
	Empfohlene Nennstichzahl / Recommended rated speed	2200 min-1
	Stichlänge / stitch length	5,0 - 8,0 mm (abhängig vom Nähmaterial / depend on fabric) Auslieferungszustand / delivery condition 8,0 mm
	Obertransport / top feed	Sägeverzahnung / saw toothing Pyramidenverzahnung / pyramid toothing optional
	gefederter Drücker / spring loaded plunger	Drückervariation optional / plunger variation optional
	Stichplattenöffnung / stitch plate opening	6,0 mm 4,5 mm optional 7,0 mm optional
	Nadelsystem / needle system Nadelstärke / needle size	GROZ-BECKERT 4669 EEO 80/12
	Fadenabschneider / thread trimmer	optional
	Fadenspannung / thread tension Faden / thread	Auslieferungszustand / delivery condition 35 cN Polyester, endlos gewirnt / polyester continuous filament 120/2
	Freiarm / support arm	Durchmesser / diameter 60 mm
	Durchgangsraum / arm space	150 mm
	Abschwenkbare Arbeitsplatte / swing away workplate	
	LED Leuchte / LED sewing lamp	
Technischer Auslieferungszustand / delivery condition:		
Riemenscheibendurchmesser Maschine/ machine pulley diameter		dw 80 mm
Motor-Leistung min. / min. motor power		500W - DA432 / DAC Classic
Keilriemen-Profil / V-belt profile		10 x 6 mm
Zahnriemenscheibe Maschine / toothed belt pulley/machine		Z = 38
Zahnriemenprofil / toothed belt profile		HTD 5M-9
Stichart / stitch type		Einfaden-Kettenstich-Blindstich Typ 103 / single thread chain stitch type 103
Anschluss pneumatisch / pneumatic connection		6 bar
Luftverbrauch, Mittelwert / average air consumption		abhängig von der Ausstattung / depending on the equipment
Stellfläche / Foot print		0,5 m x 1,1 m
Arbeitsgeräusch / operating noise at 2200 min-1 nach DIN 45635-48-1 KL3		LpAm 77 dB(A)